

**WDK 2.5****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image**

To feed through power, signal, and data is the classical requirement in electrical engineering and panel building. The insulating material, the connection system and the design of the terminal blocks are the differentiating features. A feed-through terminal block is suitable for joining and/or connecting one or more conductors. They could have one or more connection levels that are on the same potential or insulated against one another.

**General ordering data**

|            |                                                                                                                                                   |
|------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| Version    | Multi-tier modular terminal, Screw connection, dark beige, 2.5 mm <sup>2</sup> , 400 V, Number of connections: 4, Number of levels: 2, TS 35, V-0 |
| Order No.  | <a href="#">1021500000</a>                                                                                                                        |
| Type       | WDK 2.5                                                                                                                                           |
| GTIN (EAN) | 4008190169527                                                                                                                                     |
| Qty.       | 100 items                                                                                                                                         |

## WDK 2.5

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

## Approvals

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

|                       |                            |
|-----------------------|----------------------------|
| UL File Number Search | <a href="#">UL Website</a> |
|-----------------------|----------------------------|

|                      |        |
|----------------------|--------|
| Certificate No. (UR) | E60693 |
|----------------------|--------|

|                           |         |
|---------------------------|---------|
| Certificate No. (cURusEX) | E184763 |
|---------------------------|---------|

## Dimensions and weights

|                          |             |                |             |
|--------------------------|-------------|----------------|-------------|
| Depth                    | 63 mm       | Depth (inches) | 2.4803 inch |
| Depth including DIN rail | 63 mm       | Height         | 69.5 mm     |
| Height (inches)          | 2.7362 inch | Width          | 5.1 mm      |
| Width (inches)           | 0.2008 inch | Net weight     | 3.62 g      |

## Temperatures

|                                  |                |                                  |               |
|----------------------------------|----------------|----------------------------------|---------------|
| Storage temperature              | -25 °C...55 °C | Ambient temperature              | -5 °C...40 °C |
| Continuous operating temp., min. | -60 °C         | Continuous operating temp., max. | 130 °C        |

## Environmental Product Compliance

|                          |                             |                              |  |
|--------------------------|-----------------------------|------------------------------|--|
| RoHS Compliance Status   | Compliant without exemption |                              |  |
| REACH SVHC               | No SVHC above 0.1 wt%       |                              |  |
| Product Carbon Footprint | Cradle to gate              | 0.249 kg CO <sub>2</sub> eq. |  |

## Material data

|                           |       |        |            |
|---------------------------|-------|--------|------------|
| Basic material            | Wemid | Colour | dark beige |
| UL 94 flammability rating | V-0   |        |            |

## Rating data IECEx/ATEX

|                                |                   |                                 |                   |
|--------------------------------|-------------------|---------------------------------|-------------------|
| Certificate No. (ATEX)         | DEMKO15ATEX1346U  | Certificate No. (IECEX)         | IECEXULD15.0003U  |
| Max. voltage (ATEX)            | 275 V             | Current (ATEX)                  | 21 A              |
| Wire cross section max. (ATEX) | 4 mm <sup>2</sup> | Max. voltage (IECEX)            | 275 V             |
| Current (IECEX)                | 21 A              | Wire cross section max. (IECEX) | 4 mm <sup>2</sup> |
| Marking EN 60079-7             | Ex eb II C Gb     | Ex 2014/34/EU label             | II 2 G D          |

## System specifications

|                                     |                                                                                       |                               |     |
|-------------------------------------|---------------------------------------------------------------------------------------|-------------------------------|-----|
| Version                             | Screw connection,<br>for screwable cross-<br>connection, One end<br>without connector | End cover plate required      | Yes |
| Number of potentials                | 2                                                                                     | Number of levels              | 2   |
| Number of clamping points per level | 2                                                                                     | Number of potentials per tier | 1   |
| Levels cross-connected internally   | No                                                                                    | PE connection                 | No  |
| Mounting rail                       | TS 35                                                                                 | N-function                    | No  |
| PE function                         | No                                                                                    | PEN function                  | No  |

## Additional technical data

|                          |       |                             |         |
|--------------------------|-------|-----------------------------|---------|
| Open sides               | right | Number of similar terminals | 1       |
| Explosion-tested version | Yes   | Type of mounting            | Snap-on |

## WDK 2.5

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

## CSA rating data

|                               |        |                       |           |
|-------------------------------|--------|-----------------------|-----------|
| Wire cross section max. (CSA) | 12 AWG | Voltage size C (CSA)  | 300 V     |
| Current size C (CSA)          | 10 A   | Certificate No. (CSA) | 12400-135 |
| Wire cross section min. (CSA) | 26 AWG |                       |           |

## Conductors for clamping (additional connection)

Connection type, additional connection Screw connection

## Conductors for clamping (rated connection)

|                                                                                         |                      |                                                                                         |                     |
|-----------------------------------------------------------------------------------------|----------------------|-----------------------------------------------------------------------------------------|---------------------|
| Gauge to IEC 60947-1                                                                    | A3                   | Wire connection cross section AWG, max.                                                 | AWG 12              |
| Connection direction                                                                    | on side              | Tightening torque, max.                                                                 | 0.6 Nm              |
| Tightening torque, min.                                                                 | 0.4 Nm               | Stripping length                                                                        | 10 mm               |
| Type of connection 2                                                                    | Screw connection     | Type of connection                                                                      | Screw connection    |
| Number of connections                                                                   | 4                    | Clamping range, max.                                                                    | 4 mm <sup>2</sup>   |
| Clamping range, min.                                                                    | 0.05 mm <sup>2</sup> | Clamping screw                                                                          | M 2.5               |
| Blade size                                                                              | 0.6 x 3.5 mm         | Wire connection cross section AWG, min.                                                 | AWG 30              |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max. | 2.5 mm <sup>2</sup>  | Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min. | 0.5 mm <sup>2</sup> |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max. | 2.5 mm <sup>2</sup>  | Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min. | 0.5 mm <sup>2</sup> |
| Wire connection cross section, finely stranded, max.                                    | 4 mm <sup>2</sup>    | Wire connection cross section, finely stranded, min.                                    | 0.5 mm <sup>2</sup> |
| Connection cross-section, stranded, max.                                                | 4 mm <sup>2</sup>    | Connection cross-section, stranded, min.                                                | 0.5 mm <sup>2</sup> |
| Torque level with DMS electric screwdriver                                              | 1                    | Wire connection cross-section, solid core, max.                                         | 4 mm <sup>2</sup>   |
| Wire connection cross-section, solid core, min.                                         | 0.5 mm <sup>2</sup>  |                                                                                         |                     |

## Dimensions

|              |         |
|--------------|---------|
| TS 35 offset | 35.5 mm |
|--------------|---------|

## General

|                                         |               |                                         |        |
|-----------------------------------------|---------------|-----------------------------------------|--------|
| Wire connection cross section AWG, max. | AWG 12        | Wire connection cross section AWG, min. | AWG 30 |
| Standards                               | IEC 60947-7-1 | Mounting rail                           | TS 35  |

## Rating data

|                                              |                     |                                 |               |
|----------------------------------------------|---------------------|---------------------------------|---------------|
| Rated cross-section                          | 2.5 mm <sup>2</sup> | Rated voltage                   | 400 V         |
| Rated DC voltage                             | 400 V               | Nominal current                 | 24 A          |
| Current at maximum wires                     | 32 A                | Standards                       | IEC 60947-7-1 |
| Volume resistance according to IEC 60947-7-x | 2.66 mΩ             | Rated impulse withstand voltage | 6 kV          |
| Power loss in accordance with IEC 60947-7-x  | 0.77 W              | Pollution severity              | 3             |

## WDK 2.5

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## UL rating data

|                                         |        |                                         |        |
|-----------------------------------------|--------|-----------------------------------------|--------|
| Voltage size B (UR)                     | 300 V  | Current size B (UR)                     | 20 A   |
| Conductor size Factory wiring max. (UR) | 12 AWG | Current size C (UR)                     | 20 A   |
| Voltage size C (UR)                     | 300 V  | Conductor size Factory wiring min. (UR) | 22 AWG |
| Certificate No. (UR)                    | E60693 | Conductor size Field wiring min. (UR)   | 22 AWG |
| Conductor size Field wiring max. (UR)   | 12 AWG |                                         |        |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000897    | ETIM 7.0    | EC000897    |
| ETIM 8.0    | EC000897    | ETIM 9.0    | EC000897    |
| ETIM 10.0   | EC000897    | ECLASS 9.0  | 27-14-11-20 |
| ECLASS 9.1  | 27-14-11-20 | ECLASS 10.0 | 27-14-11-20 |
| ECLASS 11.0 | 27-14-11-20 | ECLASS 12.0 | 27-14-11-20 |
| ECLASS 13.0 | 27-25-01-02 | ECLASS 14.0 | 27-25-01-02 |
| ECLASS 15.0 | 27-25-01-02 |             |             |



## WDK 2.5

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Accessories

## Cross-connections

The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

## General ordering data

|            |                            |                                                                      |
|------------|----------------------------|----------------------------------------------------------------------|
| Type       | WQV 2.5/2                  | Version                                                              |
| Order No.  | <a href="#">1053660000</a> | Cross-connector (terminal), when screwed in, yellow, 32 A, Number of |
| GTIN (EAN) | 4008190031121              | poles: 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7 mm         |
| Qty.       | 50 ST                      |                                                                      |
| Type       | WQV 2.5/3                  | Version                                                              |
| Order No.  | <a href="#">1053760000</a> | Cross-connector (terminal), when screwed in, yellow, 32 A, Number of |
| GTIN (EAN) | 4008190058999              | poles: 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7 mm         |
| Qty.       | 50 ST                      |                                                                      |
| Type       | WQV 2.5/4                  | Version                                                              |
| Order No.  | <a href="#">1053860000</a> | Cross-connector (terminal), when screwed in, yellow, 32 A, Number of |
| GTIN (EAN) | 4008190049706              | poles: 4, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7 mm         |
| Qty.       | 50 ST                      |                                                                      |
| Type       | WQV 2.5/10                 | Version                                                              |
| Order No.  | <a href="#">1054460000</a> | Cross-connector (terminal), when screwed in, yellow, 32 A, Number of |
| GTIN (EAN) | 4008190135089              | poles: 10, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7 mm        |
| Qty.       | 20 ST                      |                                                                      |

## End plates and partition plates

End plates are fitted to the open side of the last modular terminal before the end bracket. The use of an end plate ensures the function of the modular terminal and the specified rated voltage. It guarantees protection against contact with live parts and makes the final terminal finger-proof.

## General ordering data

|            |                            |                                                                    |
|------------|----------------------------|--------------------------------------------------------------------|
| Type       | WAP WDK2.5                 | Version                                                            |
| Order No.  | <a href="#">1059100000</a> | End plate for terminals, dark beige, Height: 69 mm, Width: 1.5 mm, |
| GTIN (EAN) | 4008190101954              | V-0, Wemid, Snap-on: No                                            |
| Qty.       | 20 ST                      |                                                                    |
| Type       | WAP WDK2.5 BL              | Version                                                            |
| Order No.  | <a href="#">1059180000</a> | End plate for terminals, blue, Height: 69 mm, Width: 1.5 mm, V-0,  |
| GTIN (EAN) | 4008190081089              | Wemid, Snap-on: No                                                 |
| Qty.       | 20 ST                      |                                                                    |

## WDK 2.5

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Accessories

|            |                            |                                                                     |
|------------|----------------------------|---------------------------------------------------------------------|
| Type       | WTW EN                     | Version                                                             |
| Order No.  | <a href="#">1058800000</a> | Partition plate (terminal), dark beige, Height: 86 mm, Width: 3 mm, |
| GTIN (EAN) | 4008190140175              | V-0, Wemid                                                          |
| Qty.       | 20 ST                      |                                                                     |

## End bracket

Weidmüller's range of products includes end brackets that guarantee a permanent, reliable mounting on the terminal rail and prevent sliding. Versions with and without screws are available. The end brackets include marking options, also for group markers, and also a test plug holder.

## General ordering data

|            |                            |                                                                |
|------------|----------------------------|----------------------------------------------------------------|
| Type       | WEW 35/2                   | Version                                                        |
| Order No.  | <a href="#">1061200000</a> | End bracket, dark beige, TS 35, HB, Wemid, Width: 8 mm, 100 °C |
| GTIN (EAN) | 4008190030230              |                                                                |
| Qty.       | 50 ST                      |                                                                |

## Testadapter and testsockets

Test adapters and test plugs are used for the electrical connection between terminal blocks and the test equipment. In this way, an electrical contact can be established in the wired state and measurements can be done easily.

## General ordering data

|            |                            |                                                                       |
|------------|----------------------------|-----------------------------------------------------------------------|
| Type       | SL 5.08/4/WDK2.5 OR        | Version                                                               |
| Order No.  | <a href="#">1324100000</a> | Plug-in adaptor (Terminal), 5 A, Rated voltage to adjoining terminal: |
| GTIN (EAN) | 4032248144884              | 250 V, orange                                                         |
| Qty.       | 75 ST                      |                                                                       |

## WDK 2.5

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Accessories

## Warning cover

Warning covers with a flash symbol provide more safety for man and machine. They are used where external voltage must be indicated within the application.

## General ordering data

|            |                            |                                                                |
|------------|----------------------------|----------------------------------------------------------------|
| Type       | WAD 4 GE BED               | Version                                                        |
| Order No.  | <a href="#">1072000000</a> | Terminal cover, yellow, PA 66, Height: 19.8 mm, Width: 4.5 mm, |
| GTIN (EAN) | 4008190446109              | Depth: 9.6 mm, V-2                                             |
| Qty.       | 50 ST                      |                                                                |
| Type       | WAD 4 WS                   | Version                                                        |
| Order No.  | <a href="#">1072100000</a> | Terminal cover, white, PA 66, Height: 19.8 mm, Width: 4.5 mm,  |
| GTIN (EAN) | 4008190446116              | Depth: 9.6 mm, V-2                                             |
| Qty.       | 50 ST                      |                                                                |

## Blank

The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
  - Strips for fast installation
  - Terminal markers, suitable for all Weidmüller cable connectors
  - Available as blank MultiCard or with standard printing
- For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

## General ordering data

|            |                            |                                                                   |
|------------|----------------------------|-------------------------------------------------------------------|
| Type       | DEK 5/5 MC NE WS           | Version                                                           |
| Order No.  | <a href="#">1609801044</a> | Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00         |
| GTIN (EAN) | 4008190397111              | Weidmueller, white                                                |
| Qty.       | 1000 ST                    |                                                                   |
| Type       | WS 8/5 MC NE WS            | Version                                                           |
| Order No.  | <a href="#">1640740000</a> | WS, Terminal marker, 8 x 5 mm, Pitch in mm (P): 5.00 Weidmueller, |
| GTIN (EAN) | 4008190279103              | Allen-Bradley, white                                              |
| Qty.       | 720 ST                     |                                                                   |



## WDK 2.5

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Accessories

## Shield clamping saddle

With our wide range of KLBÜ shield connections, you can achieve flexible and self-adjusting shield contacting and ensure error-free plant operation.

## General ordering data

|            |                            |                      |
|------------|----------------------------|----------------------|
| Type       | LS 2.8 WDU2.5-10           | Version              |
| Order No.  | <a href="#">1056400000</a> | W-Series, Shield bus |
| GTIN (EAN) | 4008190036454              |                      |
| Qty.       | 100 ST                     |                      |

## Cross-connections

The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

## General ordering data

|            |                            |                                                                     |
|------------|----------------------------|---------------------------------------------------------------------|
| Type       | WQB A/2                    | Version                                                             |
| Order No.  | <a href="#">1578950000</a> | Cross-connector (terminal), when screwed in, black, 24 A, Number of |
| GTIN (EAN) | 4008190179557              | poles: 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 10.14 mm    |
| Qty.       | 50 ST                      |                                                                     |
| Type       | WQB A/3                    | Version                                                             |
| Order No.  | <a href="#">1578960000</a> | Cross-connector (terminal), when screwed in, black, 24 A, Number of |
| GTIN (EAN) | 4008190108960              | poles: 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 15.28 mm    |
| Qty.       | 50 ST                      |                                                                     |
| Type       | WQB A/4                    | Version                                                             |
| Order No.  | <a href="#">1578970000</a> | Cross-connector (terminal), when screwed in, black, 24 A, Number of |
| GTIN (EAN) | 4008190119522              | poles: 4, Pitch in mm (P): 5.10, Insulated: Yes, Width: 20.42 mm    |
| Qty.       | 50 ST                      |                                                                     |
| Type       | WQB A/10                   | Version                                                             |
| Order No.  | <a href="#">1578990000</a> | Cross-connector (terminal), when screwed in, black, 24 A, Number of |
| GTIN (EAN) | 4008190182663              | poles: 10, Pitch in mm (P): 5.10, Insulated: Yes, Width: 48.26 mm   |
| Qty.       | 20 ST                      |                                                                     |
| Type       | WQB A/24                   | Version                                                             |
| Order No.  | <a href="#">1579000000</a> | Cross-connector (terminal), when screwed in, black, 24 A, Number of |
| GTIN (EAN) | 4008190134211              | poles: 24, Pitch in mm (P): 5.10, Insulated: Yes, Width: 123.22 mm  |
| Qty.       | 20 ST                      |                                                                     |

## WDK 2.5

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Accessories

## Testadapter and testsockets

Test adapters and test plugs are used for the electrical connection between terminal blocks and the test equipment. In this way, an electrical contact can be established in the wired state and measurements can be done easily.

## General ordering data

|            |                            |                     |
|------------|----------------------------|---------------------|
| Type       | STB 8.5/D4/2.3/M2.5 AKZ    | Version             |
| Order No.  | <a href="#">0215700000</a> | Accessories, Socket |
| GTIN (EAN) | 4008190184872              |                     |
| Qty.       | 50 ST                      |                     |

## Marker holder

The marker holder offer the possibility of additional mounting of standard markers with a pitch of 5 or 5.1 mm. The angled holders can be optionally snapped together and could be mounted in all standard marking channels of the Klippon® Connect modular terminal blocks. Fitting marker types could be found under the respective accessories of the designation marking holder.

## General ordering data

|            |                            |                            |
|------------|----------------------------|----------------------------|
| Type       | BZT 1 WS 10/5              | Version                    |
| Order No.  | <a href="#">1805490000</a> | Accessories, Marker holder |
| GTIN (EAN) | 4032248270231              |                            |
| Qty.       | 100 ST                     |                            |
| Type       | BZT 1 ZA WS 10/5           | Version                    |
| Order No.  | <a href="#">1805520000</a> | Accessories, Marker holder |
| GTIN (EAN) | 4032248270248              |                            |
| Qty.       | 100 ST                     |                            |

## WDK 2.5

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Accessories

## WS 8/5

## WS/ DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- High flexibility thanks to manufacturer independence

## General ordering data

|            |                            |                                                   |
|------------|----------------------------|---------------------------------------------------|
| Type       | WS 8/5 MM WS               | Version                                           |
| Order No.  | <a href="#">2007150000</a> | WS, Terminal marker, 8 x 5 mm, Weidmueller, white |
| GTIN (EAN) | 4050118392029              |                                                   |
| Qty.       | 800 ST                     |                                                   |

## Testadapter and testsockets

Test adapters and test plugs are used for the electrical connection between terminal blocks and the test equipment. In this way, an electrical contact can be established in the wired state and measurements can be done easily.

## General ordering data

|            |                            |                                                           |
|------------|----------------------------|-----------------------------------------------------------|
| Type       | WTA 4N WDK 2.5             | Version                                                   |
| Order No.  | <a href="#">1878660000</a> | Test adapter (terminal), 1.5 mm <sup>2</sup> , 250 V, 6 A |
| GTIN (EAN) | 4032248503285              |                                                           |
| Qty.       | 25 ST                      |                                                           |
| Type       | WTA 4N/ZA WDK 2.5          | Version                                                   |
| Order No.  | <a href="#">1879350000</a> | Test adapter (terminal), 1.5 mm <sup>2</sup> , 250 V, 6 A |
| GTIN (EAN) | 4032248503261              |                                                           |
| Qty.       | 25 ST                      |                                                           |

**WDK 2.5****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Accessories****End plates and partition plates**

End plates are fitted to the open side of the last modular terminal before the end bracket. The use of an end plate ensures the function of the modular terminal and the specified rated voltage. It guarantees protection against contact with live parts and makes the final terminal finger-proof.

**General ordering data**

|            |                            |                              |  |
|------------|----------------------------|------------------------------|--|
| Type       | WZR WDK2.5                 | Version                      |  |
| Order No.  | <a href="#">1074000000</a> | W-Series, Intermediate frame |  |
| GTIN (EAN) | 4008190890384              |                              |  |
| Qty.       | 20 ST                      |                              |  |