

136.4122

**COVER FLANGE FOR MODULAR
DEV.**
IP40 2 MOD. 68x82x52mm



* Product image may be indicative



EN IEC 60670-1 (2021)
EN IEC 60670-1/A11 (2021)
Low voltage direct. 2014/35/EU

■ GENERAL CHARACTERISTICS

Commercial Series	UNIBOX Series
Synthetical description	COVER FLANGE FOR MODULAR DEV.

■ PHYSICAL CHARACTERISTICS

Material	THERMOPLASTIC
Working temperature	-25°C/+60°C
Protection degree IP	IP40
Protection degree IK	IK06
Colour	GREY

■ DIMENSIONAL CHARACTERISTICS

Dimensions	68x82x52mm
N.° modules	2 MOD.

■ DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]
Instruction manual

■ OPTIONS & VARIOUS NOTES

Catalogue notes	Glow-wire test: 650°C.
	Wall-mounting enclosures
	Cable inlet: 3 knock-outs Ø23 mm and one with cable gland PG16.
	Note: Versions pre-fitted with EVOLUTION Series inserts in RAL 7035 grey available upon request.
	Accepts SCAME EVOLUTION Series inserts.