

**213.3237****PLUG**

32A 3P+N+E 6h 346-415V 60Hz 50Hz  
Screw terminals



\* Product image may be indicative



EN 60309-1 (1999)

EN 60309-2 (1999)

EN 60309-1/A1 (2007)

EN 60309-1/A2 (2012)

EN 60309-2/A1 (2007)

EN 60309-2/A2 (2012)

Low voltage direct. 2014/35/EU

**GENERAL CHARACTERISTICS**

Commercial Series	OPTIMA Series
Synthetical description	PLUG

**Description**

The plug from the OPTIMA Series is designed for a rated voltage of 346-415V and a current of 32A. It features 3P+N+E poles and operates at both 50Hz and 60Hz frequencies, with a 6h hour position. The plug offers a protection degree of IP44/IP54, ensuring reliable performance in various environments. It is equipped with screw terminals and is compatible with straight type outlets. For additional customization, a version in black is available by appending ".K" to the catalogue number. This plug is engineered to meet the demands of professional applications, providing dependable connectivity and performance.

Mounting version	PORTABLE
------------------	----------

**TECHNICAL CHARACTERISTICS**

Rated current	32A
Poles	3P+N+E
Hour position	6h
Rated voltage	346-415V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

**PHYSICAL CHARACTERISTICS**

Mounting version	PORTABLE
Colour	RED
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44/IP54
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	CABLE GLAND

**DOWNLOAD**

Technical drawing [PDF]  
Technical drawing [DWG]  
Technical drawing [STP]

**OPTIONS & VARIOUS NOTES**

Catalogue notes	Version also available in black; just add ".K" at the end of the catalogue number.
-----------------	--