

**242.3297****FLUSH MOUNTING APPLIANCE  
INLET**32A 3P+N+E 6h 346-415V 60Hz 50Hz  
70X87MM Screw terminals

\* Product image may be indicative

EN 60309-2/A1 (2007)  
EN 60309-1 (1999)  
EN 60309-2 (1999)  
EN 60309-1/A1 (2007)

Low voltage direct. 2014/35/EU

**GENERAL CHARACTERISTICS**

Commercial Series	EUREKA Series
Synthetical description	FLUSH MOUNTING APPLIANCE INLET

**Description**

The flush mounting appliance inlet from the EUREKA Series is designed for a rated voltage of 346-415V and a current of 32A. Featuring 3P+N+E poles and a 6h hour position, it operates efficiently at both 50Hz and 60Hz frequencies. With a protection degree of IP44, it offers reliable performance in various environments. The inlet is equipped with screw terminals and is compatible with 90° angled outlets. This robust design ensures dependable functionality for professional applications.

Mounting version	FLUSH/SURFACE MOUNTING
------------------	------------------------

**TECHNICAL CHARACTERISTICS**

Rated current	32A
Poles	3P+N+E
Hour position	6h
Rated voltage	346-415V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

**PHYSICAL CHARACTERISTICS**

Mounting version	FLUSH/SURFACE MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44
Protection degree IK	IK07
Types of available outlets	90° ANGLED
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	PG 16

**DIMENSIONAL CHARACTERISTICS**

Flange	70X87MM
--------	---------

**DOWNLOAD**

Technical drawing [PDF]  
 Technical drawing [DWG]  
 Technical drawing [STP]