

**313.3243****CONNECTOR**

32A 2P+E 6h 200-250V 50Hz 60Hz  
Screw terminals



\* Product image may be indicative



EN 60309-1 (1999)

EN 60309-2 (1999)

EN 60309-1/A1 (2007)

EN 60309-1/A2 (2012)

EN 60309-2/A1 (2007)

EN 60309-2/A2 (2012)

Low voltage direct. 2014/35/EU

**GENERAL CHARACTERISTICS**

Commercial Series	OPTIMA Series
Synthetical description	CONNECTOR

**Description**

The connector of the OPTIMA Series is engineered for a rated voltage of 200-250V and a rated current of 32A. Featuring a 2P+E configuration and a 6h hour position, it operates efficiently at both 50Hz and 60Hz frequencies. With a protection degree of IP44/IP54, it ensures robust performance in various environments. Equipped with screw terminals and straight type outlets, it offers reliable connectivity. For an alternative aesthetic, a version in black is available by appending ".K" to the catalogue number.

Mounting version	PORTABLE
------------------	----------

**TECHNICAL CHARACTERISTICS**

Rated current	32A
Poles	2P+E
Hour position	6h
Rated voltage	200-250V
Working frequency	50Hz 60Hz
Terminals	Screw terminals

**PHYSICAL CHARACTERISTICS**

Mounting version	PORTABLE
Colour	BLUE
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44/IP54
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Cable entry	CABLE GLAND

**DOWNLOAD**

Technical drawing [PDF]  
Technical drawing [DWG]  
Technical drawing [STP]

**OPTIONS & VARIOUS NOTES**

Catalogue notes	Version also available in black; just add ".K" at the end of the catalogue number.
-----------------	--