

313.3247**CONNECTOR**

32A 3P+N+E 6h 346-415V 50Hz 60Hz
Screw terminals



* Product image may be indicative



EN 60309-1 (1999)
EN 60309-2 (1999)
EN 60309-1/A1 (2007)
EN 60309-1/A2 (2012)
EN 60309-2/A1 (2007)
EN 60309-2/A2 (2012)

Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA Series
Synthetical description	CONNECTOR

Description

The connector of the OPTIMA Series is engineered for a rated voltage of 346-415V and a rated current of 32A. Featuring a 3P+N+E configuration and a 6h hour position, it operates efficiently at both 50Hz and 60Hz frequencies. With an IP44/IP54 protection degree, it ensures robust performance in various environments. Equipped with screw terminals and straight type outlets, it offers reliable connectivity. For a different aesthetic, a version in black is available by appending ".K" to the catalogue number.

Mounting version	PORTABLE
------------------	----------

TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	3P+N+E
Hour position	6h
Rated voltage	346-415V
Working frequency	50Hz 60Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	RED
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44/IP54
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Cable entry	CABLE GLAND

DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]

OPTIONS & VARIOUS NOTES

Catalogue notes	Version also available in black; just add ".K" at the end of the catalogue number.
-----------------	--