

513.3257**SURFACE MOUNTING SOCKET**

32A 3P+N+E 6h 346-415V 60Hz 50Hz

Screw terminals



* Product image may be indicative



EN 60309-2/A1 (2007)

EN 60309-1 (1999)

EN 60309-2 (1999)

EN 60309-1/A1 (2007)

Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA-BASE Series
Synthetical description	SURFACE MOUNTING SOCKET

Description

The OPTIMA-BASE Series surface mounting socket is engineered for robust industrial applications. Featuring an angled outlet design, it accommodates a 3P+N+E configuration with a rated current of 32A and supports working frequencies of 50Hz and 60Hz. It operates within a rated voltage range of 346-415V and is positioned at 6h. The socket is designed with an IP44 protection degree, ensuring resistance to dust and splashing water. It includes screw terminals for secure connections. The product comes with an open threaded cable entry and a rubber threaded cable sleeve, enhancing installation flexibility and durability.

Mounting version	SURFACE MOUNTING
------------------	------------------

TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	3P+N+E
Hour position	6h
Rated voltage	346-415V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44
Protection degree IK	IK08
Types of available outlets	ANGLED
Contact material	CuZn (brass)
Cable entry	M32X1,5

DOWNLOAD

Technical drawing [PDF]
 Technical drawing [DWG]
 Technical drawing [STP]

OPTIONS & VARIOUS NOTES

Catalogue notes	Open threaded cable entry
	Rubber threaded cable sleeve included