

874.R2580

SLOTTED CABLE TRUNKING
25x80mm 1 WAY GREY 68mm



* Product image may be indicative



EN 50085-1 (2005)
EN 50085-2-3: 2010
EN 50085-1/A1 (2013)

Low voltage direct. 2014/35/EU

■ GENERAL CHARACTERISTICS

Commercial Series	WADO Series - Slotted Cable
Synthetical description	SLOTTED CABLE TRUNKING

Description

The WADO Series Slotted Cable Trunking, measuring 25x80mm, is engineered for efficient cable management. Featuring a single compartment with a hollow height of 68mm, it is designed for streamlined installation. The trunking is constructed in a grey finish and offers a protection degree of IK06, ensuring durability against mechanical impacts. It operates effectively within a temperature range of -5°C to +60°C, making it suitable for various environments. The short pitch design enhances flexibility in cable routing. Each standard bar is 2 meters in length, providing ample coverage for extensive installations.

Type	SHORT PITCH
------	-------------

■ TECHNICAL CHARACTERISTICS

Rated voltage	1.000V
---------------	--------

■ PHYSICAL CHARACTERISTICS

Colour	GREY
Material	THERMOPLASTIC
GLOW WIRE	GW 850°C
Self-extinguishing UL94	V0
Protection degree IK	IK06
Working temperature	-5°C/+60°C

■ DIMENSIONAL CHARACTERISTICS

Dimensions	25x80mm
Number of compartments	1 WAY
Hollow height	68mm

■ OPTIONS & VARIOUS NOTES

Catalogue notes	Standard bar length: 2m.
-----------------	--------------------------