

# Double USB socket, New Unica, 2.4A, A+C type, 2 modules, white

NU301818

### Main

Range	New Unica
Product or component type	USB charger
Device presentation	Mechanism

## Complementary

o o in promontary		
Device application	Charger	
Device mounting	Flush	
Number of modules	2 modules	
Type of USB power supply	USB type A + C	
Colour tint	White (RAL 9003)	
Surface finish	Glossy	
[Ue] rated operational voltage	100240 V AC 50/60 Hz	
Power consumption in W	0.075 W	
Nominal output power	12 W	
Input power	12 W	
Service life in hours	30000 h 12 W	
Socket number	2	
Integrated connection type	1 USB type A 5 V DC, maximum load current: 1 A 1 USB type C 5 V DC, maximum load current: 2.4 A	
Material	ABS (acrylonitrile butadiene-styrene): centre plate PC (polycarbonate) GF10 FR: casing PC (polycarbonate) GF10 FR: internal cover	
Protection type	Short-circuit protection	
Number of terminals	2 screw terminals	
Clamping connection capacity	$2 \times 0.752 \times 2.5 \text{ mm}^2$ for rigid cable(s) $2 \times 0.752 \times 2.5 \text{ mm}^2$ for flexible cable(s) $2 \times 0.752 \times 2.5 \text{ mm}^2$ for stranded cable(s)	
Wire stripping length	8 mm	
Product compatibility	All devices fulfilling the EN 62684 standard	
fixing mode	By claws By screws	
Type of packing	Flow-pack	
Ambient air temperature for operation	040 °C	
Ambient air temperature for storage	-550 °C	

Standards	ETSI EN 301 489-4 EN 60950-1 EN 62684	
Height	45 mm	
Width	22.5 mm	
Depth	42 mm	
Embedding depth	30.8 mm	
resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane	

# **Environment**

Electrical insulation class	Class II
IK degree of protection	IK04
IP degree of protection	IP20

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.900 cm
Package 1 Width	4.500 cm
Package 1 Length	4.500 cm
Package 1 Weight	54.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	6.000 cm
Package 2 Width	14.500 cm
Package 2 Length	26.000 cm
Package 2 Weight	614.000 g
Unit Type of Package 3	S01
Number of Units in Package 3	20
Package 3 Height	15.000 cm
Package 3 Width	15.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	1.399 kg

# **Contractual warranty**

Warranty (in months)



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Total lifecycle Carbon footprint	11
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

Materials and Substances		
Packaging made with recycled cardboard	Yes	
Packaging without single use plastic	No	
EU RoHS Directive	Compliant	
SCIP Number	95886af5-7adb-4240-871b-e15a1f2fef83	
REACh Regulation	REACh Declaration	


#### **Use Again**

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### NU301818

#### **Technical Illustration**

#### Wiring diagram



- A A DANGER

  HAZARD OF ELECTRIC SHOCK, EXPLOSION OR ARC FLASH
  The product must be installed and connected by a qualified electrician.
  A qualified electrician must demonstrate an in-depth knowledge of:
  Construction of electricial installations in buildings in ecoordance with IEC 60364
   Additional safety standards, local connection rules, and building regulations
   Standardized tools and measuring equipment
   Failure to follow these instructions will result in death or serious injury.

Image of product / Alternate images

#### **Alternative**



