

# Specificații



## Eaton 166523

Eaton Moeller series xPole - PL6 MCB. PL6, 4 pole, tripping characteristic: C, rated current In: 25 A, rated switching capacity IEC/EN 60898-1: 6 kA

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller series xPole - PL6 MCB
<b>CATALOG NUMBER</b>	166523
<b>EAN</b>	4015081630318
<b>PRODUCT LENGTH/DEPTH</b>	85 mm
<b>PRODUCT HEIGHT</b>	73 mm
<b>PRODUCT WIDTH</b>	70 mm
<b>PRODUCT WEIGHT</b>	0.48 kg
<b>COMPLIANCES</b>	RoHS conform
<b>MODEL CODE</b>	PL6-C25/4



Powering Business Worldwide

## Delivery program

<b>APPLICATION</b>	<ul style="list-style-type: none"> <li>• Switchgear for residential and commercial applications</li> <li>• xPole - Switchgear for residential and commercial applications</li> </ul>
--------------------	--

<b>NUMBER OF POLES</b>	Four-pole
------------------------	-----------

<b>NUMBER OF POLES (TOTAL)</b>	4
--------------------------------	---

<b>NUMBER OF POLES (PROTECTED)</b>	4
------------------------------------	---

<b>TRIPPING CHARACTERISTIC</b>	C
--------------------------------	---

<b>RELEASE CHARACTERISTIC</b>	C
-------------------------------	---

<b>AMPERAGE RATING</b>	25 A
------------------------	------

<b>TYPE</b>	<ul style="list-style-type: none"> <li>• Miniature circuit breaker</li> <li>• PL6</li> </ul>
-------------	--

## Technical Data - Mechanical

<b>WIDTH IN NUMBER OF MODULAR SPACINGS</b>	4
--	---

<b>BUILT-IN DEPTH</b>	69.5 mm
-----------------------	---------

<b>DEGREE OF PROTECTION</b>	IP20
-----------------------------	------

<b>CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MIN</b>	1 mm <sup>2</sup>
---	-------------------

<b>CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MAX</b>	25 mm <sup>2</sup>
---	--------------------

<b>CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MIN</b>	1 mm <sup>2</sup>
--	-------------------

<b>CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MAX</b>	25 mm <sup>2</sup>
--	--------------------

## Technical Data - Electrical

<b>VOLTAGE TYPE</b>	AC
---------------------	----

<b>RATED OPERATIONAL VOLTAGE (UE) - MAX</b>	230 V
---	-------

<b>RATED INSULATION VOLTAGE (UI)</b>	440 V
--------------------------------------	-------

<b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>	4 kV
---	------

<b>FREQUENCY RATING - MIN</b>	50 Hz
-------------------------------	-------

<b>FREQUENCY RATING - MAX</b>	60 Hz
-------------------------------	-------

<b>RATED SWITCHING CAPACITY (IEC/EN 60898-1)</b>	6 kA
--	------

<b>OVERVOLTAGE CATEGORY</b>	III
-----------------------------	-----

<b>POLLUTION DEGREE</b>	2
-------------------------	---

## Design verification as per IEC/EN 61439 - technical data

<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	25 A
--	------

<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT</b>	0 W
---	-----

<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT</b>	12 W
--	------

<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT</b>	0 W
---	-----

<b>HEAT DISSIPATION CAPACITY</b>	0 W
----------------------------------	-----

<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
--	--------

<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	75 °C
--	-------

## Design verification as per IEC/EN 61439

<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the

## Additional information

<b>CURRENT LIMITING CLASS</b>	3
<b>FEATURES</b>	Additional equipment possible
<b>SPECIAL FEATURES</b>	Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity
<b>USED WITH</b>	Miniature circuit breaker PL6

	temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Resurse

CATALOAGE	<a href="#">eaton-xpole-pl6-mcb-catalog-ca019069en-en-us.pdf</a> <a href="#">eaton-miniature-circuit-breaker-xpole-pl6-catalog-ca20190212-en-us.pdf</a>
CHARACTERISTIC CURVE	<a href="#">eaton-xpole-mmc4-6-mcb-characteristic-curve-004.jpg</a> <a href="#">eaton-xpole-mmc4-6-mcb-characteristic-curve-002.jpg</a>
DESENE	<a href="#">eaton-xpole-pl6-mcb-dimensions.jpg</a> <a href="#">eaton-xpole-pl6-mcb-3d-drawing-002.jpg</a>
INSTRUCȚIUNI DE INSTALARE	<a href="#">eaton-rccb-rcbo-g9-il019140zu.pdf</a>
SCHEME ELECTRICE	<a href="#">eaton-xpole-mmc4-6-mcb-wiring-diagram-006.jpg</a>

---

**DENUMIREA PROIECTULUI:**

**NUMĂRUL PROIECTULUI:**

**PREGĂTIT DE:**

**DATA:**

---



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Irlanda  
Eaton.com

© 2026 Eaton. Toate drepturile rezervate

Urmăriți-ne pe rețelele de socializare pentru a obține cele mai noi informații despre produse și asistență.

