


Specifications



Photo is representative



Eaton 278436

Eaton Moeller® series ZB Overload relay, ZB12, Ir= 1 - 1.6 A, 1 N/O, 1 N/C, Direct mounting, IP20

General specifications

PRODUCT NAME	Eaton Moeller® series ZB Thermal overload relay
---------------------	---

CATALOG NUMBER	278436
-----------------------	--------

MODEL CODE	ZB12-1,6
-------------------	----------

EAN	4015082784362
------------	---------------

PRODUCT LENGTH/DEPTH	88 mm
-----------------------------	-------

PRODUCT HEIGHT	67 mm
-----------------------	-------

PRODUCT WIDTH	45 mm
----------------------	-------

PRODUCT WEIGHT	0.141 kg
-----------------------	----------

CERTIFICATIONS	CE UL 60947-4-1 CSA File No.: 012528 UL CSA IEC/EN 60947 CSA Class No.: 3211-03 VDE 0660 IEC/EN 60947-4-1 UL Category Control No.: NKCR CSA-C22.2 No. 60947-4-1-14 UL File No.: E29184
-----------------------	---

GLOBAL CATALOG	278436
-----------------------	--------

PRODUCT TYPE	Thermal overload relay
---------------------	------------------------



Powering Business Worldwide

Product specifications

FEATURES	Phase-failure sensitivity (according to IEC/EN 60947, VDE 0660 Part 102) Trip-free release Test/off button Reset pushbutton manual/auto
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.

Resources

CATALOGS	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf Product Range Catalog Switching and protecting motors
CHARACTERISTIC CURVE	eaton-tripping-zb-overload-relay-characteristic-curve-002.eps eaton-tripping-devices-overload-relay-zb-overload-relay-characteristic-curve-004.eps
DECLARATIONS OF CONFORMITY	eaton-thermal-overload-relay-declaration-of-conformity-eu250786en.pdf eaton-thermal-overload-relay-declaration-of-conformity-uk251269en.pdf
DRAWINGS	eaton-tripping-devices-overload-relay-zb-overload-relay-dimensions-003.eps eaton-tripping-devices-overload-relay-zb-overload-relay-3d-drawing.eps
ECAD MODEL	ETN.ZB12-1,6
INSTALLATION INSTRUCTIONS	eaton-overload-relays-zb12-zb32-il03407015z.pdf IL03407195Z
MCAD MODEL	DA-CS-zb12 DA-CD-zb12
PEP ECO-PASSPORT	eaton-thermal-overload-relays-pep-eato-00458-v0101-en.pdf
SALES NOTES	eaton-dol-3phase-ac-motor-starter-ms-16a-flyer-fl034009en-en-us.pdf
WIRING DIAGRAMS	eaton-tripping-devices-overload-relay-zb-overload-relay-wiring-diagram-002.eps

10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
POLLUTION DEGREE	3
CLASS	CLASS 10 A
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC 4000 V (auxiliary and control circuits)
RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V	1.5 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V	0.9 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 110 V	0.4 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 220 V, 230 V	0.2 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V	0.9 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 60 V	0.75 A
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	1.6 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W

STRIPPING LENGTH (CONTROL CIRCUIT CABLE)	8 mm
STRIPPING LENGTH (MAIN CABLE)	10 mm
PRODUCT CATEGORY	<ul style="list-style-type: none"> • Accessories • Overload relay ZB up to 150 A
PROTECTION	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
FRAME SIZE	ZB12
ADJUSTABLE CURRENT RANGE - MAX	1.6 A
ADJUSTABLE CURRENT RANGE - MIN	1 A
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	25 °C
CONVENTIONAL THERMAL CURRENT I_{TH} OF AUXILIARY CONTACTS (1-POLE, OPEN)	6 A
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT P_{VID}	5.7 W
HEAT DISSIPATION CAPACITY P_{DISS}	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT P_{VID}	1.9 W
NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	1
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	1
NUMBER OF CONTACTS (NORMALLY CLOSED)	1

CONTACTS)	
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	1
OVERLOAD RELEASE CURRENT SETTING - MAX	1.6 A
OVERLOAD RELEASE CURRENT SETTING - MIN	1 A
RATED OPERATIONAL VOLTAGE (UE) - MAX	690 V
RATED OPERATIONAL CURRENT (IE) AT AC-15, 120 V	1.5 A
ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT	Screw connection
RESET FUNCTION	Push-button Automatic
SCREWDRIVER SIZE	1 x 6 mm, Terminal screw, Standard screwdriver 2, Terminal screw, Pozidriv screwdriver
MOUNTING METHOD	Direct attachment Direct mounting
DEGREE OF PROTECTION	IP20
OVERVOLTAGE CATEGORY	III
SAFE ISOLATION	440 V AC, Between main circuits, According to EN 61140 240 V AC, Between auxiliary contacts, According to EN 61140 440 V AC, Between auxiliary contacts and main contacts, According to EN 61140
SCREW SIZE	M3.5, Terminal screw, Control circuit cables M4, Terminal screw
SHOCK RESISTANCE	10 g, Mechanical, Sinusoidal, Shock duration 10 ms
SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 600 V)	100 kA, Fuse, SCCR (UL/CSA) 3 A, Class J/CC, max. Fuse, SCCR (UL/CSA)
SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)	R300, DC operated (UL/CSA) B600 at opposite polarity, AC operated (UL/CSA) B300 at opposite polarity, AC operated (UL/CSA)

SHORT-CIRCUIT PROTECTION RATING	6 A gG/gL, Fuse, Type "2" coordination Max. 6 A gG/gL, fuse, Without welding, Auxiliary and control circuits 25 A gG/gL, Fuse, Type "1" coordination
SUITABLE FOR	Branch circuits, (UL/CSA)
TEMPERATURE COMPENSATION	≤ 0.25 %/K, residual error for T > 40° Continuous
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	2 x (0.75 - 2.5) mm ² , Control circuit cables 1 x (0.75 - 2.5) mm ² , Control circuit cables 1 x (1 - 4) mm ² , Main cables 2 x (1 - 4) mm ² , Main cables
TERMINAL CAPACITY (SOLID)	2 x (1 - 6) mm ² , Main cables 1 x (1 - 6) mm ² , Main cables 1 x (0.75 - 4) mm ² , Control circuit cables 2 x (0.75 - 4) mm ² , Control circuit cables
TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 8, Main cables 2 x (18 - 14), Control circuit cables

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

