

Specificații



Eaton 262684

Eaton Moeller® series ETR2 Timing relay, 1W, 0.05s-100h, 24-240VAV 50/60Hz, 24-48VDC, on-delayed

General specifications

PRODUCT NAME	Eaton Moeller® series ETR2 Timing relay
CATALOG NUMBER	262684
EAN	4015082626846
PRODUCT LENGTH/DEPTH	63 mm
PRODUCT HEIGHT	70 mm
PRODUCT WIDTH	17.5 mm
PRODUCT WEIGHT	0.051 kg
CERTIFICATIONS	CSA Class No.: 3211-03 IEC/EN 60947-5-1 UL 508 UL File No.: E29184 UL UL Category Control No.: NKCR, NKCR7 CSA File No.: UL report valid Certified by UL for use in Canada CE CSA-22.2 No. 14 IEC/EN 61812-1
MODEL CODE	ETR2-11



Powering Business Worldwide

Features & Functions

ELECTRIC CONNECTION TYPE	Screw connection
FUNCTIONS	On-delayed Delay-on energization Fixed timing function

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE - MAX	60 °C

Magnet system

RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN 24 V

RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX 240 V

RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN 24 V

RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX 240 V

RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN 24 V

RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX 48 V

General information

DEGREE OF PROTECTION	IP20
NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	1
PRODUCT CATEGORY	ETR2 timing relays
SUITABLE FOR	DIN rail (top hat rail) mounting
TIME RANGE - MIN	0.05 s
TIME RANGE - MAX	360000 s
TYPE	Timer relay
VOLTAGE TYPE	AC/DC

Electrical rating

MAINS VOLTAGE TOLERANCE	24 - 240 V AC (at 50/60 Hz) 24 - 48 V DC
NOMINAL CURRENT	3 A
RATED OPERATIONAL CURRENT (IE)	3 A at 230 V (NC) 4 A at AC-15, 220 V 230 V 240 V 3 A at 230 V (NO)

Design verification

HEAT DISSIPATION CAPACITY PDISS	0 W
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to

	be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resurse

BROȘURI	EMR6 - EMT6 - ETR4 brochure
CHARACTERISTIC CURVE	eaton-timers-diagram-etr4-timing-relay-characteristic-curve.eps
DECLARATIONS OF CONFORMITY	eaton-timing-relay-declaration-of-conformity-uk251091en.pdf
DESENE	eaton-timers-timing-relay-etr2-dimensions.eps eaton-timers-timing-relay-etr2-3d-drawing.eps
MCAD MODEL	etr2_11_d.stp
SCHEME ELECTRICE	eaton-timers-timing-relay-wiring-diagram.eps

DENUMIREA PROIECTULUI:

NUMĂRUL PROIECTULUI:

PREGĂTIT DE:

DATA:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Irlanda
Eaton.com

© 2026 Eaton. Toate drepturile rezervate

Urmăriți-ne pe rețelele de socializare pentru a obține cele mai noi informații despre produse și asistență.

