

# Specifications



Photo is representative



## Eaton 277831

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 22 kW, 380 V 50 Hz, 440 V 60 Hz, AC operation, Screw terminals

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller® series DILM contactor
<b>CATALOG NUMBER</b>	277831
<b>MODEL CODE</b>	DILM50(380V50HZ,440V60HZ)
<b>EAN</b>	4015082778316
<b>PRODUCT LENGTH/DEPTH</b>	132.1 mm
<b>PRODUCT HEIGHT</b>	115 mm
<b>PRODUCT WIDTH</b>	55 mm
<b>PRODUCT WEIGHT</b>	0.872 kg
<b>COMPLIANCES</b>	CE Marked
<b>CERTIFICATIONS</b>	CSA Std. C22.2 No. 14-05 UL 508 IEC 60947-4-1 EN 60947-4-1 VDE VDE 0660 IEC/EN 60947 CSA UL
<b>CATALOG NOTES</b>	Contacts according to EN 50012
<b>PRODUCT TYPE</b>	Contactors



Powering Business Worldwide

## Features Functions

<b>NUMBER OF POLES</b>	Three-pole
------------------------	------------

## General

<b>APPLICATION</b>	Contactors for Motors
<b>DEGREE OF PROTECTION</b>	IP00
<b>FRAME SIZE</b>	FS3
<b>LIFESPAN, MECHANICAL</b>	10,000,000 Operations (AC operated)
<b>CONNECTION</b>	Screw terminals
<b>OPERATING FREQUENCY</b>	5000 mechanical Operations/h (AC operated)
<b>OVERVOLTAGE CATEGORY</b>	III
<b>POLLUTION DEGREE</b>	3
<b>PRODUCT CATEGORY</b>	Contactors
<b>PROTECTION</b>	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
<b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>	8000 V AC
<b>RESISTANCE PER POLE</b>	1.9 mΩ
<b>SUITABLE FOR</b>	Also motors with efficiency class IE3
<b>UTILIZATION CATEGORY</b>	AC-1: Non-inductive or slightly inductive loads, resistance furnaces AC-4: Normal AC induction motors: starting, plugging, reversing, inching AC-3: Normal AC induction motors: starting, switch off during running
<b>VOLTAGE TYPE</b>	AC

## Ambient conditions, mechanical

### SHOCK RESISTANCE

7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms  
 10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms  
 10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms  
 5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms  
 7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms  
 5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

## Climatic environmental conditions

<b>ALTITUDE</b>	Max. 2000 m
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	60 °C
<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN</b>	-25 °C
<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX</b>	40 °C
<b>AMBIENT STORAGE TEMPERATURE - MIN</b>	-40 °C
<b>AMBIENT STORAGE TEMPERATURE - MAX</b>	80 °C
<b>CLIMATIC PROOFING</b>	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78

## Electro magnetic compatibility

**EMITTED INTERFERENCE** According to EN 60947-1

**INTERFERENCE IMMUNITY** According to EN 60947-1

## Terminal capacities

<b>TERMINAL CAPACITY (COPPER BAND)</b>	2 x (6 x 9 x 0.8) mm (Number of segments x width x thickness), Main cables
<b>TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)</b>	2 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables 1 x (0.75 - 35) mm <sup>2</sup> , Main cables 1 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables 2 x (0.75 - 25) mm <sup>2</sup> , Main cables
<b>TERMINAL CAPACITY (SOLID)</b>	1 x (0.75 - 4) mm <sup>2</sup> , Control circuit cables 2 x (0.75 - 16) mm <sup>2</sup> , Main cables 1 x (0.75 - 16) mm <sup>2</sup> , Main cables 2 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables
<b>TERMINAL CAPACITY (SOLID/STRANDED AWG)</b>	18 - 14, Control circuit cables Single 14 - 1, double 14 - 2, Main cables
<b>TERMINAL CAPACITY</b>	1 x (16 - 50) mm <sup>2</sup> , Main

<b>(STRANDED)</b>	cables 2 x (16 - 35) mm <sup>2</sup> , Main cables
<b>STRIPPING LENGTH (MAIN CABLE)</b>	14 mm
<b>STRIPPING LENGTH (CONTROL CIRCUIT CABLE)</b>	10 mm
<b>SCREW SIZE</b>	M3.5, Terminal screw, Control circuit cables M6, Terminal screw, Main cables
<b>SCREWDRIVER SIZE</b>	0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver 2, Terminal screw, Pozidriv screwdriver
<b>TIGHTENING TORQUE</b>	3.3 Nm, Screw terminals, Main cables 1.2 Nm, Screw terminals, Control circuit cables

## Electrical rating

**RATED BREAKING CAPACITY AT 220/230 V** 500 A

**RATED BREAKING CAPACITY AT 380/400 V** 500 A

**RATED BREAKING CAPACITY AT 500 V** 500 A

**RATED BREAKING CAPACITY AT 660/690 V** 320 A

**RATED OPERATIONAL CURRENT (IE) AT AC-1, 380 V, 400 V, 415 V** 80 A

**RATED OPERATIONAL CURRENT (IE) AT AC-3, 220 V, 230 V, 240 V** 50 A

**RATED OPERATIONAL CURRENT (IE) AT AC-3, 380 V, 400 V, 415 V** 50 A

**RATED OPERATIONAL CURRENT (IE) AT AC-3, 440 V** 50 A

**RATED OPERATIONAL CURRENT (IE) AT AC-3, 500 V** 50 A

**RATED OPERATIONAL CURRENT (IE) AT AC-3, 660 V, 690 V** 32 A

**RATED OPERATIONAL CURRENT (IE) AT AC-4, 220 V, 230 V, 240 V** 21 A

**RATED OPERATIONAL CURRENT (IE) AT AC-4, 440 V** 21 A

**RATED OPERATIONAL CURRENT (IE) AT AC-4, 500 V** 21 A

**RATED OPERATIONAL CURRENT (IE) AT AC-4, 660 V, 690 V** 17 A

**RATED OPERATIONAL CURRENT (IE) AT DC-1, 60 V** 60 A

**RATED OPERATIONAL CURRENT (IE) AT DC-1, 110 V** 50 A

**RATED OPERATIONAL CURRENT (IE) AT DC-1, 220 V** 45 A

**RATED INSULATION VOLTAGE (UI)** 690 V

**RATED MAKING** 700 A

## Short-circuit rating

**SHORT-CIRCUIT CURRENT RATING (BASIC RATING)** 5 kA, 250 A max. fuse, SCCR (UL/CSA)  
5 kA, 250 A max. CB, SCCR (UL/CSA)

**SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 480 V)** 100 kA, 150 A CLASS J max. fuse, SCCR (UL/CSA)  
65 kA, 100 A max. CB, SCCR (UL/CSA)

**SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 600 V)** 100 kA, 150 A CLASS J max. fuse, SCCR (UL/CSA)

**SHORT-CIRCUIT PROTECTION RATING (TYPE 1 COORDINATION) AT 400 V** 160 A gG/gL

**SHORT-CIRCUIT PROTECTION RATING (TYPE 1 COORDINATION) AT 690 V** 80 A gG/gL

**SHORT-CIRCUIT PROTECTION RATING (TYPE 2 COORDINATION) AT 400 V** 80 A gG/gL

**SHORT-CIRCUIT PROTECTION RATING (TYPE 2 COORDINATION) AT 690 V** 63 A gG/gL

---

**CAPACITY UP TO 690 V  
(COS PHI TO IEC/EN  
60947)**

---

**RATED OPERATIONAL  
POWER AT AC-3, 240 V, 50  
HZ** 17 kW

---

**RATED OPERATIONAL  
POWER AT AC-3, 380/400  
V, 50 HZ** 22 kW

---

**RATED OPERATIONAL  
POWER AT AC-3, 415 V, 50  
HZ** 30 kW

---

**RATED OPERATIONAL  
POWER AT AC-3, 440 V, 50  
HZ** 32 kW

---

**RATED OPERATIONAL  
POWER AT AC-3, 500 V, 50  
HZ** 36 kW

---

**RATED OPERATIONAL  
POWER AT AC-3, 690 V, 50  
HZ** 30 kW

---

**RATED OPERATIONAL  
POWER AT AC-4, 220/230  
V, 50 HZ** 6 kW

---

**RATED OPERATIONAL  
POWER AT AC-4, 240 V, 50  
HZ** 6.5 kW

---

**RATED OPERATIONAL  
POWER AT AC-4, 415 V, 50  
HZ** 11 kW

---

**RATED OPERATIONAL  
POWER AT AC-4, 440 V, 50  
HZ** 12 kW

---

**RATED OPERATIONAL  
POWER AT AC-4, 500 V, 50  
HZ** 13 kW

---

**RATED OPERATIONAL  
POWER AT AC-4, 660/690  
V, 50 HZ** 14 kW

---

**RATED OPERATIONAL  
VOLTAGE (UE) AT AC -  
MAX** 690 V

---

## Conventional thermal current I<sub>th</sub>

**CONVENTIONAL  
THERMAL CURRENT I<sub>TH</sub>  
(1-POLE, ENCLOSED)** 145 A

**CONVENTIONAL  
THERMAL CURRENT I<sub>TH</sub>  
(3-POLE, ENCLOSED)** 58 A

**CONVENTIONAL  
THERMAL CURRENT I<sub>TH</sub>  
AT 55°C (3-POLE, OPEN)** 68 A

**CONVENTIONAL  
THERMAL CURRENT I<sub>TH</sub>  
OF MAIN CONTACTS (1-  
POLE, OPEN)** 162 A

## Magnet system

**ARCING TIME** 10 ms

**DROP-OUT VOLTAGE** AC operated: 0.6 - 0.3 x  
UC, AC operated

**DUTY FACTOR** 100 %

**PICK-UP VOLTAGE** 0.8 - 1.1 V AC x U<sub>c</sub>

**POWER CONSUMPTION,  
PICK-UP, 50 HZ** 149 VA, Dual-frequency  
coil in a cold state and 1.0  
x U<sub>s</sub>, at 50 Hz

**POWER CONSUMPTION,  
PICK-UP, 60 HZ** 178 VA, Dual-frequency  
coil in a cold state and 1.0  
x U<sub>s</sub>, at 60 Hz

**POWER CONSUMPTION,  
SEALING, 50 HZ** 4.1 W, Dual-frequency coil  
in a cold state and 1.0 x  
U<sub>s</sub>, at 50 Hz  
16 VA, Dual-frequency coil  
in a cold state and 1.0 x  
U<sub>s</sub>, at 50 Hz

**POWER CONSUMPTION,  
SEALING, 60 HZ** 4.1 W, Dual-frequency coil  
in a cold state and 1.0 x  
U<sub>s</sub>, at 60 Hz  
19 VA, Dual-frequency coil  
in a cold state and 1.0 x  
U<sub>s</sub>, at 60 Hz

**RATED CONTROL SUPPLY  
VOLTAGE (US) AT AC, 50  
HZ - MIN** 380 V

**RATED CONTROL SUPPLY  
VOLTAGE (US) AT AC, 50  
HZ - MAX** 380 V

**RATED CONTROL SUPPLY  
VOLTAGE (US) AT AC, 60  
HZ - MIN** 440 V

**RATED CONTROL SUPPLY  
VOLTAGE (US) AT AC, 60  
HZ - MAX** 440 V

**SWITCHING TIME (AC  
OPERATED, MAKE  
CONTACTS, CLOSING  
DELAY) - MIN** 12 ms

**SWITCHING TIME (AC  
OPERATED, MAKE  
CONTACTS, CLOSING  
DELAY) - MAX** 18 ms

**SWITCHING TIME (AC  
OPERATED, MAKE  
CONTACTS, OPENING  
DELAY) - MIN** 8 ms

**SWITCHING TIME (AC  
OPERATED, MAKE  
CONTACTS, OPENING  
DELAY) - MAX** 13 ms

## Communication

<b>CONNECTION TO SMARTWIRE-DT</b>	No
-----------------------------------	----

## Safety

<b>SAFE ISOLATION</b>	440 V AC, Between the contacts, According to EN 61140 440 V AC, Between coil and contacts, According to EN 61140
-----------------------	---

## Contacts

<b>NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)</b>	0
--	---

<b>NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)</b>	0
--	---

## Design verification

<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>	9.9 W
---	-------

<b>HEAT DISSIPATION CAPACITY PDISS</b>	0 W
--	-----

<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>	3.3 W
--	-------

<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	50 A
--	------

<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>	4.1 W
---	-------

<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
------------------------------------	--

<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
---	--

<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
---	--

<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
---	--

<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
---	--

<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
-----------------------	--

<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
---------------------------------	--

<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
----------------------------	--

<b>10.3 DEGREE OF PROTECTION OF</b>	Does not apply, since the entire switchgear needs to
-------------------------------------	--

<b>ASSEMBLIES</b>	be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Resources

	<a href="#">Product Range Catalog</a> <a href="#">Switching and protecting motors</a>
CATALOGS	<a href="#">SmartWire-DT Catalog</a> <a href="#">eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf</a>
CHARACTERISTIC CURVE	<a href="#">eaton-contactors-switch-dilm-characteristic-curve-002.eps</a> <a href="#">eaton-contactors-component-dilm-characteristic-curve-003.eps</a> <a href="#">eaton-contactors-switch-dilm-characteristic-curve.eps</a>
DECLARATIONS OF CONFORMITY	<a href="#">eaton-contactor-declaration-of-conformity-eu250742en.pdf</a> <a href="#">eaton-contactor-declaration-of-conformity-uk251225en.pdf</a>
DRAWINGS	<a href="#">eaton-contactors-dilm-dimensions-012.eps</a> <a href="#">eaton-contactors-mounting-dilm-dimensions.eps</a> <a href="#">eaton-contactors-mounting-dilm-dimensions-002.eps</a> <a href="#">eaton-contactors-dilm-dimensions-002.eps</a> <a href="#">eaton-contactors-dilm-3d-drawing-011.eps</a> <a href="#">eaton-contactors-mounting-dilm-3d-drawing.eps</a> <a href="#">eaton-general-ie-ready-dilm-contactor-standards.eps</a>
ECAD MODEL	<a href="#">ETN.277831.edz</a>
INSTALLATION INSTRUCTIONS	<a href="#">IL03407033Z</a>
INSTALLATION VIDEOS	<a href="#">WIN-WIN with push-in technology</a>
MCAD MODEL	<a href="#">DA-CD-dil m40 72</a>

	<a href="#">DA-CS-dil_m40_72</a> <a href="#">dil_m40_65_22.dwg</a>
PEP ECO-PASSPORT	<a href="#">eaton-iec-contactors-pep-eato-00126-v0101-en.pdf</a>
SYSTEM OVERVIEW	<a href="#">eaton-contactors-dilm-contactor-system-overview.eps</a>
WIRING DIAGRAMS	<a href="#">eaton-contactors-contact-dilm-wiring-diagram-003.eps</a>

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

---



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

