

Specifications

Photo is representative

Eaton 293988

Eaton Moeller® series DILK Contactor for capacitors, with series resistors, 12.5 kVAR, 230 V 50 Hz, 240 V 60 Hz

General specifications

PRODUCT NAME	Eaton Moeller® series DILK capacity contactor
CATALOG NUMBER	293988
MODEL CODE	DILK12- 11(230V50HZ,240V60HZ)
EAN	4015082939885
PRODUCT LENGTH/DEPTH	138 mm
PRODUCT HEIGHT	135 mm
PRODUCT WIDTH	45 mm
PRODUCT WEIGHT	0.51 kg
WARRANTY	1 year
CERTIFICATIONS	CSA File No.: 012528 CE CSA-C22.2 No. 60947-4-1-14 UL Category Control No.: NLDX UL File No.: E29096 IEC/EN 60947 UL UL 60947-4-1 IEC/EN 60947-4-1 CSA CSA Class No.: 3211-04
PRODUCT TYPE	Capacity contactor



Powering Business Worldwide

Features Functions

FITTED WITH: Series resistors

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MIN -25 °C

AMBIENT OPERATING TEMPERATURE - MAX 60 °C

AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN -25 °C

AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX 40 °C

Terminal capacities

TERMINAL CAPACITY (FLEXIBLE WITH FERRULE) 1 x (0.75 - 16) mm², Main cables

TERMINAL CAPACITY (SOLID) 1 x (0.75 - 16) mm², Main cables

TERMINAL CAPACITY (SOLID/STRANDED AWG) 18 - 6, Main cables

TERMINAL CAPACITY (STRANDED) 1 x 16 mm², Main cables

General

APPLICATION Contactors for power factor correction

DEGREE OF PROTECTION IP00

LIFESPAN, ELECTRICAL 150,000 Operations

CONNECTION Screw terminals

OPERATING FREQUENCY 120 Operations/h

PRODUCT CATEGORY DILK Contactors for capacitors

PROTECTION Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

VOLTAGE TYPE AC

Electro magnetic compatibility

EMITTED INTERFERENCE According to EN 60947-1

INTERFERENCE IMMUNITY According to EN 60947-1

Electrical rating

RATED OPERATIONAL CURRENT (IE) 18 A at 400 V (three-phase capacitors, open)
18 A at 525 V (three-phase capacitors, open)
18 A at 230 V (three-phase capacitors, open)
18 A at 690 V (three-phase capacitors, open)
16 A at 525 V (three-phase capacitors, enclosed)
16 A at 690 V (three-phase capacitors, enclosed)
16 A at 400 V (three-phase capacitors, enclosed)
16 A at 230 V (three-phase capacitors, enclosed)

Switching capacity

SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)	10 A, 600 V AC, (UL/CSA) 1 A, 250 V DC, (UL/CSA)
---	---

SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)	A600, AC operated (UL/CSA) P300, DC operated (UL/CSA)
--	--

Magnet system

ARCING TIME	10 ms
DROP-OUT VOLTAGE	AC operated: 0.6 - 0.3 x UC, AC operated
DUTY FACTOR	100 %
PICK-UP VOLTAGE	0.8 - 1.1 V AC x U _c
POWER CONSUMPTION, PICK-UP, 50 HZ	58 VA, Dual-frequency coil in a cold state and 1.0 x U _s , at 50 Hz
POWER CONSUMPTION, PICK-UP, 60 HZ	71 VA, Dual-frequency coil in a cold state and 1.0 x U _s , at 60 Hz
POWER CONSUMPTION, SEALING, 50 HZ	2.1 W, Dual-frequency coil in a cold state and 1.0 x U _s , at 50 Hz 7.6 VA, Dual-frequency coil in a cold state and 1.0 x U _s , at 50 Hz
POWER CONSUMPTION, SEALING, 60 HZ	9.3 VA, Dual-frequency coil in a cold state and 1.0 x U _s , at 60 Hz 2.1 W, Dual-frequency coil in a cold state and 1.0 x U _s , at 60 Hz
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN	230 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX	230 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN	240 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX	240 V
SWITCHING TIME (AC OPERATED, MAKE CONTACTS, CLOSING DELAY) - MIN	16 ms
SWITCHING TIME (AC OPERATED, MAKE CONTACTS, CLOSING DELAY) - MAX	22 ms
SWITCHING TIME (AC OPERATED, MAKE CONTACTS, OPENING DELAY) - MAX	14 ms

Contacts

**MAKING CAPACITY
WITHOUT DAMPING (I-
PEAK VALUE)** 180 x I_e

**NUMBER OF AUXILIARY
CONTACTS (NORMALLY
CLOSED CONTACTS)** 1

**NUMBER OF AUXILIARY
CONTACTS (NORMALLY
OPEN CONTACTS)** 1

Special purpose ratings

**SPECIAL PURPOSE
RATING OF CAPACITOR
SWITCHING** 18 A, 240 V 60 Hz 3phase,
(UL/CSA)
15 kVar, 600 V 60 Hz
3phase, (UL/CSA)
7.5 kVar, 240 V 60 Hz
3phase, (UL/CSA)
15 kVar, 480 V 60 Hz
3phase, (UL/CSA)
18 A, 480 V 60 Hz 3phase,
(UL/CSA)
14.4 A, 600 V 60 Hz
3phase, (UL/CSA)

Design verification

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	2.1 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0.7 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	18 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	2.1 W
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.

Resources

	Product Range Catalog Switching and protecting motors
CATALOGS	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf SmartWire-DT Catalog
DECLARATIONS OF CONFORMITY	eaton-capacity-contactor-declaration-of-conformity-uk251239en.pdf eaton-capacity-contactor-declaration-of-conformity-eu250756en.pdf eaton-contactors-dilk-dimensions-004.eps eaton-contactors-dilk-dimensions.eps eaton-contactors-mounting-dilm-dimensions.eps
DRAWINGS	eaton-contactors-mounting-dilm-dimensions-002.eps eaton-contactors-dilk-dimensions-002.eps eaton-contactors-dilk-3d-drawing.eps
ECAD MODEL	DA-CE-ETN.DILK12-11(230V50HZ,240V60HZ)
INSTALLATION INSTRUCTIONS	IL03407038Z
INSTALLATION VIDEOS	WIN-WIN with push-in technology eaton-dilk12-25-drawing.dwg
MCAD MODEL	eaton-dilk12-25-3d-model.stp DA-CD-dil m17 38
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - 293988
WIRING DIAGRAMS	eaton-contactors-circuit-dilk-wiring-diagram-002.eps

10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

